

Natural Stone Sealer



- USE ON SANDSTONE, LIMESTONE, GRANITE AND SLATE
- USES NANO-PENETRATION TECHNOLOGY
- CLEAR PROTECTIVE SEAL AGAINST WATER, OIL, GREASE AND STAINS
- BREATHABLE
- QUICK DRYING
- FOR INTERNAL AND EXTERNAL USE

Dirt Defence Natural Stone Sealer is an advanced formula, high performance sealer using the latest fluoropolymer technology to provide a waterproof, breathable transparent, durable seal to natural stone such as sandstone, limestone and granite. Solvent free and easy to use, Dirt Defence Natural Stone Sealer repels dirt, oil, stains, grease and inhibits the growth of moss and algae.



BENEFITS

- Long lasting fluoropolymer technology • Resists fungal growth & staining
- Protects and waterproofs • Improves slip resistance • Quick drying
- Transparent finish

BEFORE TREATMENT

Ensure that the surface to be treated is clean and free of any contaminants including oil, grease, algae and efflorescence. This product is not suitable if surfaces have been treated previously with a silicone or stearate based water repellent.

APPLICATION

- Always test a small inconspicuous area before use to ensure surface compatibility, performance and finish/texture is acceptable
- Shake container before use
- Ensure surface is thoroughly dry and dust free before application
- Do not pour Dirt Defence Natural Stone Sealer directly onto paving. Apply by brush, roller or airless garden sprayer with fan pattern spray attachment, applying an even coat and avoiding runs or puddles by removing excess product from the surface
- For porous surfaces, apply 2 coats, the second within 2 hours after the first

COVERAGE

4-6m² per litre dependent on the porosity of the surface.

CLEANING

Clean brushes, rollers and other equipment immediately after use with soapy water. Remove as much product as possible from application equipment before cleaning.

STORAGE

24 months from the date of manufacture in original unopened container in a clean, dry area. Do not store below 5°C.

IMPORTANT

- Do not apply when ambient/surface temperature is below +10°C
- Do not apply in wet weather, when rain is imminent or before surface is completely dry
- Optimum performance is reached after 2-3 days. Allow product to cure overnight before subjecting to heavy use – increase this time in cold, damp conditions
- Always test a small inconspicuous area before use to ensure surface compatibility, performance and finish/texture is acceptable
- Not suitable for non porous surfaces e.g. quarry tiles, engineering brick, polished or glazed surfaces
- Keep pets away until surface is fully dry
- Protect from frost and store above +5°C in ventilated area away from heat source

