

ENVIROMOSE HEAVY DUTY WATER BASED PAINT REMOVER

FOR PROFESSIONAL AND DIY USE

THERE IS NO SAFER AND MORE EFFECTIVE STRIPPER ON THE MARKET

- Strips Paint, Varnish, Artex, Stains and Lacquers
- Strips from Wood, Metal, Brick, Stone and Fibreglass
- Removes ALL graffiti
- Even removes carpet adhesive residues from floors
- Internal and External use
- Water based and non-flammable
- Non-corrosive, non-ozone depleting
- Widely adopted by professional stripping companies, contractors and decorators
- Safe to handle and store
- Solves all Health & Safety and Risk Assessment issues

Disclaimer

We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products may be used. This information is given in good faith without warranty. Users are advised to make their own test to determine the safety and suitability of each product combination for their own purposes. Any additional information required for clarification is freely available from Chemicals Ltd.



Available in
5 litre, 2 litre, 1 litre and 500ml bottles

For more information about Enviromose, Paramose or any other stripping or coating products from Chemicals Ltd contact

Chemicals Ltd
PO Box 88 Southport
Merseyside PR8 5LH
England

tel: 44 (0)1704 880800
fax: 44 (0)1704 880900
email: sales@paintstripper.com
www.paintstripper.com



enviromose™



PRO GRADE PAINT STRIPPER



EXTRA STRONG GEL

THE NEW SAFER WAY TO STRIP

INTERNAL PAINT • MASONRY PAINT • VARNISH

GRAFFITI • ARTEX® • STAINS • LACQUER



Water based, low odour paint stripper

an easy to use white gel with a pleasant almond odour

- Slow drying
- Non flammable
- Non Ozone depleting
- Non Corrosive
- Cost effective
- Low V.O.C
- Excellent methylene chloride replacement

STRIPS

- Wood
- Metal
- Brick
- Stone
- Fibreglass

EXTERNAL Uses

- Buildings
- Boats
- Railings
- Graffiti
- Wood stain (decking, sheds etc)

INTERNAL Uses

- Class O upgrade schemes
- Staircases
- Walls
- Ceilings
- Artex
- Graffitiw

Other substrates?

Call our technical support team on
01704 880800

ALWAYS
APPLY A THICK
GENEROUS
COAT

DO NOT
SPREAD
PRODUCT
TOO FAR AS IT
CAN RESULT
IN POOR
PENETRATION

LET
ENVIROMOSE
DO THE WORK
FOR YOU - THE
LONGER YOU
LEAVE IT, THE
MORE IT WILL
STRIP

NEVER LET THE
PRODUCT DRY
OUT

ENVIROMOSE
CAN BE LEFT
ON OVERNIGHT
- COVER WITH
PLASTIC TO
AVOID DRYING
OUT

COVERAGE: APPROX 1 - 4m² PER LITRE

Always test a small area before use.

Always read Health and Safety Data before use.

FOR BEST PERFORMANCE, USE BETWEEN 15-30° C

HOW LONG DOES IT TAKE TO WORK?

Varnish	15 - 60 minutes
Paint	10 - 60 minutes
Two pack varnish	30 minutes - 2 hours
Heavy multi-layered paint	90 minutes - overnight
Two pack lacquer	30 minutes - 4 hours
Graffiti	5 minutes - 4 hours
Artex	1 - 4 hours

PREPARATION

- Ensure surfaces to be stripped are dry - always protect floors and delicate surfaces.

HOW TO USE

- Cover top with a cloth during opening to avoid splashes.
- Layer a generous, even coat of Enviromose onto surface to be stripped.
- Apply with a suitable clean brush or airless spray (rollers can be used for light coatings) - do not brush out
- Leave for approx 2 hours and apply a second generous coat. (On less than five layers of paint or varnish, a second coat may not be necessary.)
- After product has penetrated the substrate (up to 24 hours) scrape off with suitable scrapers, leaving surface as clean as possible,
- Rinse clean with cold water and a stainless steel scourers and leave to dry. Never use steel wool - stainless steel only.

NOTE: ENVIROMOSE WORKS QUITE DIFFERENTLY FROM TRADITIONAL STRIPPERS. IT NEEDS TO BE LEFT IN PLACE AND WORKS FROM THE BOTTOM UP, THUS OFTEN AVOIDING REPEATED SCRAPING AND REAPPLICATION. IT IS THEREFORE VERY ECONOMICAL IN APPLICATION, BUT REQUIRES A CHANGE IN TECHNIQUE.