

# WATERSEAL

## FOR WOOD



1. OVERVIEW  
WHAT IS WATERSEAL FOR WOOD?
2. TECHNICAL DATA  
HOW TO USE

## A VERSATILE TREATMENT FOR WOOD:

---

Waterseal for Wood is considered to be the ultimate protection against water and dirt ingress, prolonging the life of wooden substrates by up to 5x their usual life cycle.

It is suitable for use in all settings, around the home & DIY projects are made easy by this simple application, whilst industrial and larger areas can be treated allowing a hard wearing & easy to maintain seal.

DD2 Water wrap technology means that active ingredients work together to bond tightly to pores of the wood, creating a strong chain cross linked bonds to instantly repel water, it enables each droplet of water, to be instantly pushed to the surface of the wood, preventing all forms of dirt and water ingress.

Ideal for use on:

- Decking & Fencing
- Cladding & Untreated Flooring
- Wood Furniture
- Garden Furniture
- Marine Decking
- Summer Houses & Garden Sheds



# HOW TO USE:

---

## Precautions for use:

Always test on a small hidden portion of the surface to be cleaned to check compatibility and performance before commencing with the whole area

Do NOT apply to hot surfaces or in strong direct sunlight. DO NOT allow the product to dry in between applications. Not suitable for non porous substrates.

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)

## Important:

Test a small area before use, to ensure the final result is satisfactory. Remove surface contamination. All algae and mould should be treated and removed using Algae Remover. Ensure surface is dry before

## Curing:

Allow 2 hours. Fully dry after 24 hours. NB. Longer curing periods may be required when applied in cooler conditions.

A high performance, penetrating, water repellent sealer for porous & untreated wood. Formulated using the latest technology to give outstanding results.

Provides a hard wearing invisible, protective seal against water, oil, stains, efflorescence etc... on both horizontal and vertical surfaces.

- Provides a hard wearing, invisible, protective seal and primer.
- Can be used on both horizontal and vertical surfaces.
- No change to the texture or colour of the surface.
- Allows substrate to breathe so moisture can escape.
- UVA resistant.
- For internal and external use.
- Resists the growth of mould and algae.

- 1.** Apply with a low pressure spray or brush from bottom to top on vertical surfaces, at a spread rate of 4-5m<sup>2</sup> per litre. Ensure an even, wet coat to the point of saturation
- 2.** Apply an even wet on wet coat to the point of saturation, once the first coat starts to soak in, allowing for deeper penetration into the substrate. Do not allow the product to dry in between applications.
- 3.** Avoid runs drips or puddling by removing excess product from the surface. Allow to cure for 2 hours - 24 hours before subjecting to heavy use on horizontal surfaces.