

# Decking Slip-Resist Sealer

- PROVIDES SLIP-RESISTANCE WHEN DECKING IS WET
- USES MICRO-BARRIER TECHNOLOGY
- DOES NOT CHANGE THE APPEARANCE OF THE DECKING
- PROTECTS AND PRESERVES DECKING
- REDUCES SILVERING OF THE WOOD
- EASY TO APPLY - SAFE TO USE
- WATER BASED - CONTAINS NO ABRASIVES

Enviromose Decking Slip-Resist Sealer is an advanced, high performance penetrating sealer, using the latest micro traction technology to provide a waterproof, breathable, transparent seal to wood and decking.

## BENEFITS

The unique formulation reduces the amount of slippery algae growth without changing the appearance of the timber.

- Solvent free and easy to use • Repels moisture • Long lasting technology
- Reduces the growth of moss and algae • Protects and waterproofs
- Resists fungal growth & staining • Quick drying • Transparent finish

## BEFORE TREATMENT

Ensure that the surface to be treated is clean and free of any contaminants including oil, grease, algae and mould. Algae spores must be treated with a good quality biocide such as Enviromose paving and decking cleaner before proceeding.

## APPLICATION

- Always test a small inconspicuous area before use to ensure surface compatibility, performance and finish/texture is acceptable
- Shake container before use
- Ensure surface is thoroughly dry and dust free before application
- Do not pour directly onto the surface. Apply by brush or roller
- Apply a generous even coat, avoiding runs or puddles by removing excess product from the surface. Apply a second coat within 2 hours after the first

## COVERAGE

4-6m<sup>2</sup> per litre dependent on the porosity of the surface.

## CLEANING

Clean brushes, rollers and other equipment immediately after use with soapy water.

## STORAGE

24 months from the date of manufacture in original unopened container in a clean, dry area. Do not store below 5°C.



## HEALTH & SAFETY

- Keep out of reach of children.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Do not get in eyes, on skin, or on clothing.
- Do not eat, drink or smoke when using this product.
- IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
- IF ON SKIN: wash with plenty of soap and water, get medical advice/attention.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, get immediate medical advice/attention.

## IMPORTANT

- Do not apply when ambient/surface temperature is below +10°C.
- Do not apply in wet weather, when rain is imminent or before substrate is completely dry
- Optimum performance is reached after 3 days. Allow product to cure overnight before subjecting to heavy use – increase this time in cold, damp conditions
- Not suitable for non porous surfaces e.g. quarry tiles, engineering brick, polished or glazed surfaces
- Keep pets away until surface is fully dry

