

## PARAMOSE

Paramose products have over 25 years of development, founding the base for the chemicals ltd ranngge to flourish.

We are constantly tresting and trying out new ways to better our products, contimnusily improving our range with the latest available technologys day by day, allowing us to become leaders in the formulation and development of paint removers, paint stripper and surface coating removers.

Our unique range of paint and coating removers have all been independently tested by the leading professionals in the industry to ensure they comply fully with the very latest health and safety regulations.

---

## EMAIL

[sales@paintstripper.com](mailto:sales@paintstripper.com)

## PHONE

01704 880800

## WEB

[www.paintstripper.com](http://www.paintstripper.com)

# How to use: Paramose

PARAMOSE  
PAINT & VARNISH  
REMOVER

# PARAMOSE

## PAINT & VARNISH REMOVER

Powerful wood stripper for paint and varnish etc, used by craftsmen and professionals in the wood finishing, furniture restoration and antiques trades. Does not dry quickly or darken wood. Will remove multi - coat systems with ease.

Our low evaporation formula allows for extremely deep penetration through tough layers to remove coatings and paints.

## BEENFITS

Low Evaporation • No Need To Neutralise • Easy to Apply • Will Not Raise Grain • Will Not Darken Wood

Ideal for use on: Wood, Metal, Aluminium, Marble, Slate, Solvent Based Paints, Water Based Paints, Varnish, Polyurethane Lacquers, Two Pack Epoxy, Industrial Paints, Powder Coating



# How to use Paramose Paint & Varnish Remover:

## SURFACE PREPERATION

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory. Ensure the surface(s) to be stripped are dry before applying. Protection should be provided for coatings that you do not wish to remove or any surface that may be damaged by the product.

## APPLICATION

1. This product should not be used outside of an industrial facility or only by a registered professional. Wear suitable gloves, goggles and protective clothing. Cover the lid with a cloth and hold away from face during opening. Pour some Paramose into a suitable container and replace top of can. Read and follow the Health & Safety Data Sheets as detailed in the separate MSDS document

2. Apply a generous even coat by brush. Do not over-brush. Leave between 20 - 40 minutes until the product reacts with the paint or varnish.

3. For multi layered surfaces (5 or more), a second coat of paint and varnish stripper is recommended. Use a dabbing motion, without the need to remove the first coat.

4. Check at intervals to see how the paint remover is working and remove softened paint with a scraper. Rub down with coarse wire wool, on wood follow the grain.

## CLEANING OF EQUIPMENT

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.

## IMPORTANT

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)

EUROPEAN REGULATIONS 455/2009/EC DICHLOROMETHANE PAINT REMOVERS ARE ONLY TO BE USED FOR INDUSTRIAL USE WHILST IN AN INDUSTRIAL ENVIRONMENT. OR BY A TRAINE DREFISTERED PROFESSIONAL.

The definition of Industrial is 'Facilities where paint stripping takes place'. Examples would be units and workshops used for stripping articles with either dip tanks or brush applied systems.

Professional use allowed only under the following conditions:  
For use, by specifically trained professionals, trained in the appropriate provisions for the protection of the health and safety including a requirement that a professional shall hold a certificate that is accepted by the Member State in which that professional operates, so as to demonstrate proper training and competence to safely use paint strippers containing dichlo- romethane.

## PRECAUTIONS FOR USE

Read and follow the Health & Safety Data Sheets as detailed in the separate MSDS document. Ensure adequate ventilation at all times, vapours are heavier than air so extractors should be at low level.

Paramose P&V must be shaken well before use. Always apply generous even coats. Do not try to spread the product too far, as this will result in poor penetration and faster evaporation. Allow Paramose P&V to do its work. Do not use in confined spaces. Do not try to remove too quickly. Never let the surface become too dry during treatment

## STORAGE

Keep out of reach of children. Keep in a dry place between 5°C and 25°C in the original container.

## Customer Projects:

### PARAMOSE USED ON WOOD

A restoration project completed using Paramose  
Paint & Varnish Remover on wood panelling



### RESTORATION

Paramose P&V (paint and varnish) remover is ideal for professional restoration projects on all types of jobs - no matter how big or small.