

PRO GRADE Paint Stripper

A fast acting and safer to use, waterbased double strength paint remover. Suitable for use on a wide range of surfaces and coatings

Removes sealers and coatings safely and effectively without damaging the surface. Strips a wide variety of surfaces and coatings including: Paint & Varnish, Artex, Stains & Lacquer, Graffiti and Carpet adhesive residues from floors

Surface Preparation

Always test an inconspicuous area before use to ensure the compatibility and finished result is acceptable. Ensure the surface(s) to be stripped are dry before applying the Enviromose Pro Grade Paintstripper. Protection should be provided for floor coatings that you do not wish to remove or any surface that may be damaged by the remover i.e. perspex, plastics, rubber

How to use

Cover the top with a cloth during opening to avoid splashes.

- Layer a generous, even coat of Enviromose onto the surface to be stripped.

- Apply with a suitable clean brush or airless spray (rollers can be used for light coatings) DO NOT BRUSH OUT

- Leave for approximately 2 hours and apply a second generous coat. (On less than five layers of Paint or Varnish, a second coat may not be necessary).

- After the product has penetrated the substrate (up to 24 hours) scrape off with suitable scrapers, leaving surface as clean as possible.

- Rinse clean with cold water containing detergent and a stainless steel scourer, leave to dry. Never use steel wool - stainless steel only.

Guide of Stripping Times

Varnish: 15 - 60 minutes

Paint: 10 - 60 minutes

Two pack varnish: 30 minutes - 3 Hours

Heavy multi-layered paint: 90 minutes - Overnight

Two pack lacquer: 30 minutes - 24 Hours

Graffiti: 5 minutes - 4 Hours

Artex: 1 - 4 Hours

Precautions for use

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).



Benefits

- For internal & external use
- Safer and easy to use
- Water based and non-flammable
- Non-corrosive, non-ozone depleting
- Extra strong for tougher finishes
- Fast acting
- Eco-friendly
- Low VOC

Storage

Keep out of reach of children
Keep in a dry place between 5°C and 30°C in the original container.

Cleaning of equipment

Clean tools and equipment immediately after use with water. Always read safety instructions before use.

Product Characteristics

| | |
|--------------------------|---|
| Colour | Clear |
| Odour | Barely Perceptible |
| Form | Liquid |
| Specific Gravity @ 25°C | 1.01 |
| Shelf Life | 24 Months from the date of manufacture in the original unopened container - protect from frost |
| PH | 5 |
| Application Temperatures | Between +5°C and 30°C |
| Coverage | 1 litre will strip 1-3 m ² dependant on thickness and amount of layers / coatings to be stripped |