



R10B1 Paint Stripper

Extra Strength, low odour, fast acting paint remover formulated using the latest technology. New faster working formula removes paint, graffiti, sealers and coatings safely and effectively without damaging the surface. Suitable for internal and external use.

Important Information:

Always test an inconspicuous area before use to ensure the compatibility and finished result is acceptable. Protection should be provided for floor coatings that you do not wish to remove or any surface that may be damaged by i.e. perspex, plastics, rubber etc.

Guide of stripping times:

- Graffiti: 5 minutes - 2 hours
- Varnish: 10 - 30 minutes
- Paint: 5 - 30 minutes
- Two pack varnish: 15 - 90 minutes
- Heavy multi-layered paint: 45 minutes 12 hours
- Two pack lacquer: 15 minutes - 12 Hours
- Artex: 30 minutes - 2 Hours

How to use:

Paramose R10/B1 is supplied ready to use and should not be diluted. Ensure the surface is completely dry before application. Cover the top with a cloth during opening to avoid splashes.

Layer a generous, even coat onto the surface using a clean brush or airless spray (rollers can be used for light coatings) DO NOT BRUSH OUT

Leave for the recommended timing dependant on the stripping guide and apply a second generous coat. (On less than five layers of Paint or Varnish, a second coat may not be necessary).

After the product has penetrated the substrate (up to 24 hours) scrape off with suitable scrapers, leaving surface as clean as possible.

Rinse clean with cold water containing detergent and a stainless steel scourer, leave to dry. Never use steel wool - stainless steel only.

Precautions for use:

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

Cleaning of equipment:

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.



Perfect for use on:

- Graffiti
- Paint & Varnish
- Artex
- Stains & Lacquer
- Carpet adhesive residues from floors

Benefits:

- Safer and easy to use
- Water based and non-flammable
- Non-corrosive, non-ozone depleting
- Extra strong for tougher finishes
- Fast acting
- Eco-friendly
- Low VOC

Storage:

Keep out of reach of children
Keep in a dry place between 5°C and 30°C
in the original container.

Product Characteristics

Colour	White
Odour	Barely Perceptible
Form	Liquid
PH	Approx. 4.5 - 5
Specific Gravity @ 25°C	1.01
Shelf Life	24 Months from the date of manufacture in the original unopened container - protect from frost
Application Temperatures	Minimum +5°C Maximum 30°C
Coverage	1 litre will strip 1m ² dependant on thickness and amount of layers / coatings to be stripped