



AS10

Ahesive + Coating Remover

Paramose AS10 is an advanced blend of water washable polar and non polar solvents containing thickening agents, evaporation retardants and stabilisers that have been specially formulated to remove hard wearing paints and coatings from substrates.

Paramose AS10 quickly and effectively removes :

- graffiti • automotive paint • two pack lacquers • heat resistant finishes • powder coatings •

Important Information:

Read and follow the Health & Safety Data Sheets as detailed in the separate MSDS document. Ensure adequate ventilation at all times, DCM vapours are heavier than air so extractors should be at low level. Paramose AS10 must be shaken well before use. Always apply generous even coats. Do not try to spread the product too far, as this will result in poor penetration and faster evaporation. Allow Paramose AS10 to do its work. Do not use in confined spaces. Do not try to remove too quickly. Never let the surface become too dry during treatment

Surface Preparation

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory and to calculate consumption. Protection should be provided for areas you do not wish to strip.

How to use:

Consult MSDS before proceeding. Wear suitable gloves, goggles and protective clothing.

- Cover the lid with a cloth and hold away from face during opening
- Pour Paramose into a suitable container and replace top of can
- Apply a generous even coat by brush do not over brush
- Leave for between 20 - 40 minutes until the product reacts with the paint or varnish.
- For multi layered surfaces (5 or more), a second coat of Paramose AS10 is recommended. Use a dabbing motion, without the need to remove the first coat.
- Check at intervals to see how the AS10 is working and remove softened paint with a scraper.
- Power wash clean with cold water.

Precautions for use:

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)

EUROPEAN REGULATIONS 455/2009/EC DICHLOROMETHANE PAINT REMOVERS ARE ONLY TO BE USED FOR INDUSTRIAL USE WHILST IN AN INDUSTRIAL ENVIRONMENT. The definition of Industrial is 'Facilities where paint stripping takes place'. Examples would be units and workshops used for stripping articles with either dip tanks or brush applied systems.

Cleaning of equipment:

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.



Perfect for use on:

Due to its thicker formulation, Paramose AS10 is ideal for use on vertical surfaces. It is particularly suitable for use in warmer climates due to its specially designed evaporation retardants. Used by professionals on:

- cars • masonry • wood • motorbikes • machinery • floors •

Benefits:

- Powerful and effective stripper
- Fast acting
- Cost effective
- Removes most paint, adhesives and lacquered finishes
- Removes multiple layers at a time
- Concentrated for a high performance
- Non Flammable
- Non Caustic

Storage:

Keep out of reach of children

Keep in a dry place between 5°C and 30°C in the original container.

Product Characteristics

Colour	Clear
Odour	DCM
Form	Light Gel
PH	11
Specific Gravity @ 25°C	1.01
Shelf Life	24 Months from the date of manufacture in the original unopened container - protect from frost
Application Temperatures	Minimum +5°C Maximum 30°C
Boiling Point	38°C
Flash Point	>93°C
Coverage	Coverage rates vary with porosity: 4-6m ² per litre