



# Paramose Industrial Paint & Varnish Stripper

PRODUCT CODE R103



REMOVES SEALERS AND COATINGS SAFELY AND EFFECTIVELY WITHOUT DAMAGING THE SURFACE. STRIPS A WIDE VARIETY OF SURFACES AND COATINGS INCLUDING:

- PAINT & VARNISH
- ARTEX
- STAINS & LACQUER
- GRAFFITI
- CARPET ADHESIVE RESIDUES FROM FLOORS

Removes paint from wood, metal and exterior structures, due to its thickness is ideal for use on vertical surfaces such buildings, cars, trucks, cladding, steelwork etc.

## BENEFITS

- For internal & external use • Safer and easy to use
- Water based and non-flammable • Non-corrosive, non-ozone depleting
- Extra strong for tougher finishes • Fast acting
- Eco-friendly • Low VOC

## APPLICATION

- Cover the top with a cloth during opening to avoid splashes.
- Always test a small inconspicuous area before use to ensure the final results are satisfactory.
- Layer a generous, even coat of Enviromose onto the surface to be stripped.
- Apply with a suitable clean brush or airless spray (rollers can be used for light coatings) DO NOT BRUSH OUT
- Leave for approximately 2 hours and apply a second generous coat. (On less than five layers of Paint or Varnish, a second coat may not be necessary).
- After the product has penetrated the substrate (up to 24 hours) scrape off with suitable scrapers, leaving surface as clean as possible.
- Rinse clean with cold water containing detergent and a stainless steel scourer, leave to dry. Never use steel wool - stainless steel only.

## COVERAGE

1-3m<sup>2</sup> per litre dependent on the porosity of the surface.

## CLEANING

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.

## STORAGE

24 months from the date of manufacture in original unopened container in a clean, dry area. Do not store below 5°C.



## HEALTH & SAFETY

- EUROPEAN REGULATIONS 455/2009/EC DICHLOROMETHANE PAINT REMOVERS ARE ONLY TO BE USED FOR INDUSTRIAL USE WHILST IN AN INDUSTRIAL ENVIRONMENT.
- For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS). EUROPEAN REGULATIONS 455/2009/EC DICHLOROMETHANE PAINT REMOVERS ARE ONLY TO BE USED FOR INDUSTRIAL USE WHILST IN AN INDUSTRIAL ENVIRONMENT. The definition of Industrial is 'Facilities where paint stripping takes place'. Examples would be units and workshops used for stripping articles with either dip tanks or brush applied systems.

