

TS10 HEAVY DUTY DCM PAINT & VARNISH REMOVER

(RESTRICTED TO INDUSTRIAL USE ONLY)



OVERVIEW

Water washable tank stripper is suitable for use as a tank stripper or in conjunction with the Paramose Flo-Through machine. Its special formulation will remove most multi layered paint, varnishes and coatings quickly and cost effectively.

Ideal for stripping doors, furniture, alloy wheels etc.. It is designed to remove varnish, twin pack, paints, epoxy adhesive, bitumen and lacquers. Suitable for both hardwood and softwood.

BENEFITS

- Powerful and effective stripper
- Fast acting
- Cost effective
- Removes most paint, adhesives and lacquered finishes
- Removes multiple layers at a time
- Non Caustic

IMPORTANT / LIMITATIONS

Ensure there is effective ventilation in all processing areas, in particular for the wet processing and the drying of stripped articles: local exhaust ventilation at strip tanks supplemented by forced ventilation in those areas, so as to minimise exposure and to ensure compliance, where technically feasible, with relevant occupational exposure limits;

Measures to minimise evaporation from strip tanks comprising: lids for covering strip tanks except during loading and unloading; suitable loading and unloading arrangements for strip tanks; and wash tanks with water or brine to remove excess solvent after unloading;

Measures for the safe handling of dichloromethane in strip tanks comprising: pumps and pipework for transferring paint stripper to and from strip tanks; and suitable arrangements for safe cleaning of tanks and removal of sludge;

Personal protective equipment that complies with Directive 89/686/EEC comprising: suitable protective gloves, safety goggles and protective clothing.

PRODUCT CHARACTERISTICS

Colour	Off White
Odour	DCM
Form	Liquid
Specific Gravity @ 25°C	1.25
Evaporation rate	High
Application Temperatures	Minimum +5°C Maximum 30°C
Shelf Life	24 months from the date of manufacture in the original unopened container
Boiling point	35°C

SURFACE PREPERATION

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory and to calculate consumption.

APPLICATION

Ideally apply out of direct sunlight

Using a flo through machine:
Stand object in tray and apply TS10 working from the bottom up.

Allow TS10 to soak in for 5 minutes and then reapply again working from the bottom upwards, washing off the coating with stripper as you go.

When most of the old surface is removed or loosened leave to drain for 1-2 minutes

Using a tank:
Submerge item(s) at least 25mm below surface

Allow the excess to drip back into the tank

Remove residue with cold water and allow to dry



PRECAUTIONS FOR USE

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS)

STORAGE

Keep out of reach of children

Keep in a dry place between 5°C and 30°C in the original container.

CLEANING OF EQUIPMENT

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.

