



## Gloss Sealer

Hybrid Gloss Sealer is formulated with the latest copolymer dispersion of acrylic and methacrylic esters cross-linked with a multi phase, self cross linking polyester-polyurethane copolymer.

Designed to give low water absorption after relatively low curing times.

This hybrid formulation forms a film which will give a gloss finish, that's easy to clean and maintain. Use on block paving, patios and driveways.

### Important

R158 is unable to work if applied over non-absorbent surfaces. Do not apply if rain is expected within 4 hours or before the surface is completely dry. Subsequent coats must be applied wet on wet. Do not apply during rain or frost and when surface air temperature is <5°C and > 30°C

### Surface Preparation

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory and to calculate consumption.

Surface should be clean, dry and free from dirt, soiling mould and algae before applying.

### Precautions for use:

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

### How to use:

Apply an even, wet coat to the point of saturation, once the first coat starts to soak in, apply a further wet on wet coat, 1 to 3 applications recommended. This method gives deeper penetration into the substrate.

Avoid pooling, by mopping up excess product.

### Storage

KEEP OUT OF THE REACH OF CHILDREN.

Store in a cool, well ventilated area. Keep container tightly closed. Storage temperature between 8°C and 30°C.

### Curing

Water repellence is evident after initial curing but may take up to 7 days to reach 100% efficiency.



### Perfect for use on:

- Polycarbonate
- PVC
- Plastic
- Fibreglass
- Coated metal cladding
- Paint

### Benefits:

- Water based
- Easy to apply and safer to use  
Virtually odourless  
Colour enhancing  
Good water resistance

### Cleaning of Equipment

Clean tools and equipment immediately after use with water.

### Product Characteristics

Colour	Milky
Odour	Slight
Form	Liquid
Coverage	Coverage depends on the porosity of the surface and its texture approximately 4 - 6m <sup>2</sup> per litre
Application Temperature	Between 10°C and 25°C
Shelf Life	24 Months from the date of manufacture in the original unopened container
PH	7
Specific Gravity @ 25 °C	1.00