

Stone Colour Enhancer

- FOR USE ON NATURAL STONE PAVING
- USES NANO-REFRACTIVE TECHNOLOGY
- CLEAR PROTECTIVE SEAL AGAINST WATER, OIL, GREASE AND STAINS
- BREATHABLE
- QUICK DRYING

Enviromose Stone Colour Enhancer is an advanced formula, high performance sealer using the latest technology to provide a waterproof, breathable transparent, durable seal to black stone. Solvent free and easy to use, Enviromose Stone Colour Enhancer helps to repel dirt, stains, and inhibits the growth of moss and algae.

BENEFITS

- Resists fungal growth & staining • Improves slip resistance
- Protects and waterproofs • Transparent finish • Quick drying

BEFORE TREATMENT

Ensure that the surface to be treated is clean and free of any contaminants including oil, grease, algae and efflorescence. This product is not suitable if surfaces have been treated previously with a silicone or stearate based water repellent.

APPLICATION

- Shake container before use
- Ensure surface is thoroughly dry and dust free before application
- Do not pour Black Limestone Colour Enhancer directly onto paving. Apply by brush, roller or airless garden sprayer with fan pattern spray attachment, applying a thin but even coat and avoiding runs or puddles by removing excess product from the surface
- For porous surfaces, apply 2 coats, the second within 30 minutes of the first, ensuring both coats are uniform and any excess surface material is completely dispersed

COVERAGE

4-6m² per litre dependent on the porosity of the surface.

CLEANING

Clean brushes, rollers and other equipment immediately after use with soapy water. Remove as much product as possible from application equipment before cleaning.

STORAGE

24 months from the date of manufacture in original unopened container in a clean, dry area. Do not store below 5°C.



HEALTH & SAFETY

- Keep out of reach of children.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Do not get in eyes, on skin, or on clothing.
- Do not eat, drink or smoke when using this product.
- IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
- IF ON SKIN: wash with plenty of soap and water, get medical advice/attention.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, get immediate medical advice/attention.

IMPORTANT

- Do not apply when ambient/surface temperature is below +10°C
- Do not apply in wet weather, when rain is imminent or before surface is completely dry
- Optimum performance is reached after 2-3 days. Allow product to cure overnight before subjecting to heavy use – increase this time in cold, damp conditions
- Always test a small inconspicuous area before use to ensure surface compatibility, performance and finish/texture is acceptable
- Not suitable for non porous surfaces e.g. quarry tiles, engineering brick, polished or glazed surfaces
- Keep pets away until surface is fully dry
- Protect from frost and store above +5°C in ventilated area away from heat source

