



SUPREME

Surface Treatment

A step above standard protection, an invisible sealer that will protect against all forms of contamination with ease.

Dirt Defence SUPREME provides extremely long lasting protection, preventing ingress of most types of surface contamination, with the help of Dirt Defence technologies. It will provide superior resistance to oil, water and graffiti to all types of porous wall & floor building substrates.

How to Use

Apply with a low pressure spray from bottom to top on vertical surfaces, taking care not to allow the product to run. Ensure an even, wet coat to the point of saturation

Apply an even wet on wet coat to the point of saturation, once the first coat starts to soak in. Between 1 - 3 applications are recommended, allowing for deeper penetration into the substrate

Avoid runs drips or puddling by removing excess product from the surface. Allow to cure for 48 hours - 7 days before subjecting to heavy use

Surface Preparation

Always test a small hidden area of the substrate before use, to ensure the final result is satisfactory and to calculate consumption. Cracks must be repaired using a concrete/mortar repair system. Ensure surface is clean, free from dust, dirt, oil, efflorescence, organic growth and old paint films. Pressure washing up to 2500 PSI and the use of algae remover will eradicate residual organic spores. Efflorescence must be treated with salt defence before applying.

Storage

KEEP OUT OF THE REACH OF CHILDREN.

Keep in a dry place. Do not store below 5°C. Keep out of direct sunlight and protect from frost.

Important

R175/A sealer is unable to work if applied over non-absorbent surfaces. Ensure substrate moisture is 5% maximum. Do not apply if rain is expected within 24 hours. Do not apply during rain or frost and when surface air temperature is <5°C and > 30°C.

Coverage

Coverage rates vary with substrate porosity:

Architectural Concrete 5 m² per litre

Block Paving 5 - 8 m² per litre

Porous Natural Stone (Limestone/Sandstone) 8 - 16 m² per litre

Low Porosity Stone (Granite, Marble, Slate, Terra-cotta) 8 - 16 m² per litre



Benefits

- Resist moss and lichen formation
- Will not alter the appearance of the surface
- Gives moisture vapour permeable treatment
- Reduce freeze-thaw effects which can lead to long term lasting damage
- Contains no PFOA or PFOS ingredients
- UV resistant, non flammable & environmentally friendly
- Water, oil, stain and UV resistant
- Reduce surface degradation
- Prevents airborne contamination from sticking to the surface

Precautions for use

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

Cleaning of Equipment

Clean tools and equipment immediately after use with water.

Product Characteristics

Colour	White
Odour	Barely perceptible
Form	Liquid
Application Temperature	Between 10°C and 25°C
Shelf Life	24 months from date of manufacture in the original unopened container.
Curing	Water repellence is evident after initial curing but may take up to 7 days to reach 100% efficiency.