Marble Slip-Resist Sealer

• PROVIDES SLIP-RESISTANCE WHEN MARBLE IS WET

- USES MICRO-BARRIER TECHNOLOGY
- DOES NOT CHANGE THE APPEARANCE OF THE DECKING
- PROTECTS AND PRESERVES
- EASY TO APPLY AND DOES NOT CHANGE THE APPEARANCE OF THE SURFACE
- WATER BASED CONTAINS NO ABRASIVES

Enviromose Marble Slip-Resist Sealer is an advanced, high performance, penetrating sealer, using the latest micro traction technology to provide slip reduction on wet slippery floors without changing the appearance, ideal for use on marble, granite, laminates and polished natural surfaces without etching or changing the appearance.

BENEFITS

- Solvent free and easy to use Non etching Protects Breathable
- Easy to maintain Resists staining UV stable Ideal for use in wet areas as well as corridors, lobby areas, kitchens and bathrooms

BEFORE TREATMENT

Ensure that the surface to be treated is clean and free of any contaminants including oil and grease before proceeding.

APPLICATION

- Always test a small inconspicuous area before use to ensure surface compatibility, performance and finish/texture is acceptable
- · Shake container before use
- . Ensure surface is thoroughly dry and dust free before application
- \bullet Do not pour directly onto the surface. Apply by brush or roller treating up to $2m^2$ at a time
- Apply an even coat, avoiding runs or puddles by removing excess product from the surface. Leave to dry 5-10 minutes before buffing with a microfibre cloth

COVERAGE

4-6m² per litre dependent on the porosity of the surface.

CLEANING

Clean brushes, rollers and other equipment immediately after use with soapy water. **STORAGE**

24 months from the date of manufacture in original unopened container in a clean, dry area. Do not store below 5°C.



HEALTH & SAFETY

- Keep out of reach of children.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Do not get in eyes, on skin, or on clothing.
- Do not eat, drink or smoke when using this product.
- IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
- IF ON SKIN: wash with plenty of soap and water, get medical advice/attention.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, get immediate medical advice/attention.

IMPORTANT

- Do not apply when ambient/surface temperature is below +10°C.
- Do not apply in wet weather, when rain is imminent or before substrate is completely dry
- Optimum performance is reached after 3 days. Allow product to cure overnight before subjecting to heavy use – increase this time in cold, damp conditions
- Keep pets away until surface is fully dry

