



RESTORE

Block Paving Restorer

A water based penetrating concrete block treatment, its penetrating formula works in different ways to protect and colour the substrate without the use of high levels of resin and polymers.

Ingredients penetrate into the substrate to give long lasting protection, secondary ingredients colour the surface for a restored finish. In addition a water proofing agent sits close to the surface to give improved weather protection for a long lasting finish.

Surface Preparation

Ensure the surface to be treated is dry, clean, free from any contaminants including dust, dirt, oil, grease, algae and mould. Algae, moss and spores must be treated and removed with a good quality algicide designed for this purpose, all residues of the algicide need to be removed and allowed to dry before applying the treatment, use a power washer to remove the dirt and grime from between the gaps.

How to use:

Always test a small inconspicuous area before treating the whole surface. Follow all instructions for the test area, only proceed once satisfied that the compatibility, look, finish, performance are acceptable.

- Shake container before use
- Ensure surface is thoroughly dry and clean before proceeding
- Do not pour directly onto the surface. Apply a generous even coat using a brush or long pile roller, ensuring even distribution.
- For older or more porous surfaces, once the first coat has started to soak in (within 1 hour) apply a second coat, remove any heavy pooling.
- Leave to dry for 24 hours.

Storage

KEEP OUT OF THE REACH OF CHILDREN. Store in a cool, well ventilated area. Keep container tightly closed. Storage temperature between 8°C and 30°C.

Important

Do not apply when ambient/surface temperature is below 10°C or above 25°C. Do not apply in wet weather, when rain is imminent or before surface is completely dry. Clean regularly with a non-abrasive cleaner to maintain the visual appearance of the treated surface. The product is designed to be long lasting and to improve over time, tests have shown many years protection.



Benefits:

- Colour restoration
- Easy to use
- Repels moisture
- Reduces the growth of moss and algae
- Available in different colours
- Easy to use

Coverage

The product will continue to cure and bond with the substrate for the next 7 days, after this period the performance will still continue to improve over the following weeks.

Precautions for use:

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

Product Characteristics

Colour	Depending on colour. Colours available - Black/ Brown/Clear
Odour	Barely perceptible
Form	Liquid
Coverage	Spread rates vary dependant on the type and age of the substrate. NEW - 4 - 6m ² per litre OLD - 3 - 5m ² per litre
Application Temperature	Between 8°C and 25°C
Shelf Life	24 Months from the date of manufacture in the original unopened container
PH	7
Specific Gravity @ 25 °C	1.00