



# Polycarbonate Protector Spray

A waterbased, easy to use, self curing, cross linking spray on sealant that protects and restores the look of polycarbonate, PVC, vinyl cladding, paint and many more surfaces.

This unique non film forming formulation is simply applied, to give extended protection against weather damage as well as enhanced appearance that covers fine swirls and scratches.

Reactive micro ingredients in the formulation chemically bond to both organic and inorganic materials to give long lasting protection against damage caused by harsh environmental elements.

## Important

Always test a small inconspicuous area before use, to ensure surface compatibility, performance and finish is acceptable.

Surface should be clean and dry before application.

Do not use on hot surfaces, ideal surface temperature is between 10°C and 25°C.

Do not use if rain is due within 12 hours.

Protect surfaces which are not to be treated.

Full performance to be reached after 24 hours.

## Precautions for use:

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

## How to use:

This product is supplied ready to use and should not be diluted. Shake well before use.

Spray a light even coat to the clean surface.

Work in with a microfibre cloth, overlapping as you go, leaving an even film. Leave for 30 seconds.

Buff with a dry microfibre cloth.

Repeat the process for more damaged or porous areas to give extra protection.

## Storage

KEEP OUT OF THE REACH OF CHILDREN.

Store in a cool, well ventilated area. Keep container tightly closed. Storage temperature between 8°C and 30°C.



## Perfect for use on:

- Polycarbonate
- PVC
- Plastic
- Fibreglass
- Coated metal cladding
- Paint

## Benefits:

- Extends the life of the substrate.
- Extends UV protection.
- Improves appearance covering fine scratches.
- Improves weather resistance.
- Helps resist dirt build up.
- Makes surfaces easier to clean.
- Non film forming/bonds to surface.
- Breathable.
- Improves scratch resistance.

## Product Characteristics

Colour	Milky
Odour	Slight
Form	Liquid
Coverage	Up to 20m <sup>2</sup> per 500ml Spray
Application Temperature	Between 10°C and 25°C
Shelf Life	24 Months from the date of manufacture in the original unopened container
PH	7
Specific Gravity @ 25 °C	1.00