



PURE MARBLE

Marble Acid Resist Sealer

A step above standard protection, the surface becomes fully resistant to acidic compounds, atmospheric pollution and oil contamination

Proven and tested to protect marble from all forms of staining

Dirt Defence Pure Marble is an acid resistance treatment specifically designed for Marble surfaces. It will prevent any damage being caused to the surface by laying down a nano barrier that prevents any contaminants to enter into the pores of the substrate.

This product is applicator approved and should only be applied by trained professionals using the recommended equipment.

Surface Preparation

Ensure the pre-testing procedure has been carried out before applying to establish whether a base coat is required. Make sure this test is carried out each time a new surface is treated as there will be varying levels of porosity.

Clean the surface with our pre-clean solution ensuring it is completely dry and free of dust and any contaminants, we recommend using a tack cloth to do this just before applying a base coat or top coat.

Application

Apply using a HVLP spraying system following the method directed during training.

Cleaning of Equipment

Clean the spraying equipment immediately after each use using Dirt Defence Gun Wash ensuring all components have been cleaned.

Storage

Keep out of reach of children
Keep in a dry place between 10°C and 25°C in the original container.
If a container is resealed, ensure the thread of the bottle is wiped clean and the lid is resealed tight after use

Precautions for use

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).



Product Characteristics

Colour	Clear
Odour	Low
Form	Liquid
Coverage	Approximately 6-7m ² per litre dependant on temperature and humidity.
Application Temperature	Between 10°C and 25°C
Shelf Life	6 Months from the date of manufacture in the original unopened container.
Curing	The surface will be touch dry in 1 hour, 100% cured after 7 days.

Limitations

Only suitable for use by trained professionals
Once applied this product can not be removed from the surface.

When choosing to seal a substrate with Dirt Defence Pure Marble its important to test for porosity, if the substrate has no porosity then its probably already got a sealer applied.

Remember each slab of stone is unique, later deliveries can often vary from showroom samples so we recommend that each slab is tested prior to application using our test procedure to indicate how porous the substrate is. Details of the pre-testing procedure can provided upon request