

Wood Protector



- HIGH PERFORMANCE PROTECTION AGAINST WATER PENETRATION
- USES NANO-PENETRATION TECHNOLOGY
- REDUCES SILVERING AND ALGAE GROWTH
- UV RESISTANT
- SUITABLE FOR ALL CLEAN AND PREPARED WOOD SURFACES

Dirt Defence Wood Protector is a penetrating treatment for wood, giving extended protection against water penetration. A treated surface remains breathable enabling residual moisture to escape as vapour.

USES

- Suitable for clean and prepared wood surfaces
- Provides excellent protection against water penetration
- Treated surfaces remain breathable
- Reduces algae growth
- UV resistant
- Reduces silvering

APPLICATION

- Always carry out a test on an agreed trial area to ensure Wood Protector is both suitable and delivers the required performance
- Ensure the surface to be treated is clean and free of all dust, soiling, organic growth and salt deposits
- Surface and air temperature need to be $>6^{\circ}\text{C}$
- Externally, wood protector is not to be applied during damp and wet weather or if rain is imminent and avoid applying to hot surfaces $>40^{\circ}\text{C}$ or in strong, direct sunlight
- Shake the container well before opening
- Ensure the surface is visibly dry before application
- Apply with a brush or roller, ensuring an even application
- 2 applications are required, the second being within 2 hours of the first
- Splashing product onto adjacent surfaces should be wiped off immediately with a soft dry cloth

COVERAGE

4-6m² per litre dependent on the porosity of the surface.

CLEANING

Clean brushes, rollers and other equipment immediately after use with soapy water.

STORAGE

24 months from the date of manufacture in original unopened container in a clean, dry area. Do not store below 5°C .

