



## PROTECT + MAINTAIN

# Grout and Tile Protector

Provides long term protection keeping maintenance low allowing for easier cleaning, ideal for bathrooms, kitchens and patios.

Grout and Tile Protector is an impregnating invisible sealer that prevents ingress of most types of surface contamination, including water, dirt and grime to all types of porous tiles, stone and grout.

### Surface Preparation

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory and to calculate consumption. Allow the test patch to weather before proceeding to coat the whole area. Remove surface contamination. Surface should be clean, free from dust, dirt, oil, efflorescence, organic growth, coatings and water sealers. All algae and mould should be treated and removed.

### Precautions for use:

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

### How to use:

Grout and Tile protector is supplied ready to use and should not be diluted. Shake well before use.

- Apply an even, wet saturated coat.
- Once the first coat starts to soak in, apply a further wet on wet coat. This method gives deeper penetration into the substrate.
- Avoid runs, drips or puddling by removing excess product from the surface.
- **DO NOT allow the product to dry in between applications.**

### Storage

KEEP OUT OF THE REACH OF CHILDREN.

Store in a cool, well ventilated area. Keep container tightly closed. Storage temperature between 8°C and 30°C.

### Important

This product is unable to work if applied over non- absorbent coated or painted surfaces.

### Cleaning of Equipment

Clean tools and equipment immediately after use with water. Always read safety instructions before use.



### Perfect for use on:

- Polycarbonate
- PVC
- Plastic
- Fibreglass
- Coated metal cladding
- Paint

### Benefits:

- Breathable and long lasting.
- Invisible
- Restricts fungal growth and algae
- UV Resistant
- Non-Flammable.
- Environmentally friendly.

### Curing

Water repellence is evident after initial curing but may take up to 7 days to reach 100% efficiency.

### Product Characteristics

Colour	Clear
Odour	Barely Perceptible
Form	Liquid
Application Temperature	Between 5°C and 30°C
Shelf Life	24 Months from the date of manufacture in the original unopened container
PH	9-9.5
Specific Gravity @ 25 °C	1.00