



MAXIMUM PROTECTION

Waterseal for Masonry

Provides a hard wearing invisible, protective seal against water, oil, stains, efflorescence and much more on both horizontal and vertical surfaces.

Waterseal is a high performance, penetrating, repellent sealer specially designed for porous substrates such as; concrete, render, bricks and most other calcium based materials. Formulated using the latest technology to give outstanding performance and durability. Ideal for damp external walls, buildings and most structures

Surface Preparation

Remove surface contamination and ensure all algae and mould have been treated and removed prior application. Surface must be completely dry before application.

Precautions for use:

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

How to use:

Ready to use product, do not dilute.

- Shake container well, apply liberally using a brush or garden sprayer
- Ensure the surface is saturated at a spread rate of 4-5m² per litre. Once the first coat starts to soak in, apply a further wet on wet coat. This method gives deeper penetration into the surface. Do not allow the product to dry in-between applications.
- Avoid runs, drips or puddling by removing excess product from the surface using a clean lint free cloth
- Leave to dry. Surface should be touch dry within 2 hours and fully dry after 24 hours.
- For decking and flooring please allow 24 hours before subjecting to heavy traffic.

Storage

Keep out of reach of children. Keep in a dry place between 5°C and 30°C in the original container.

Important

Always test on a small hidden portion of the surface to be treated to check compatibility and performance before commencing with the whole area. Unable to work if applied to non-porous surfaces e.g. polished or glazed surfaces. Keep children and pets away until the treatment is complete and the surface is completely dry. Do not apply if rain is expected within 4 hours or before the surface is completely dry. Do not apply to hot surfaces or in direct sunlight.

Cleaning of Equipment

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.



Perfect for use on:

- Concrete
- Render
- Bricks
- Block Paving
- Natural Stone
- And many more!

Benefits:

- Breathable and long lasting.
- Invisible
- Restricts fungal growth and algae
- UV Resistant
- Non-Flammable.
- Environmentally friendly.

Curing

Water repellence is evident after initial curing but may take up to 7 days to reach 100% efficiency.

Product Characteristics

Colour	White
Odour	Barely Perceptible
Form	Liquid
Application Temperature	Between 5°C and 30°C
Shelf Life	24 Months from the date of manufacture in the original unopened container
PH	7
Specific Gravity @ 25 °C	1.01