



MAXIMUM PROTECTION

Acrylic Sealer

A water borne dual core acrylic polymer to give outstanding performance on most surfaces. It provides a hard wearing and weatherproof seal to block paving, paths and patios. Available in a satin finish, Dirt Defence Acrylic Sealer stabilises the substrate, repels dirt, oil, fuel stains, enhances the surface finish and inhibits the growth of moss and algae.

A solvent free sealer that penetrates deep into the substrate, improving the lifetime of the surface and decreasing erosion whilst enhancing the surface colour. It is hard wearing and makes the surface easier to clean. A single application will provide a low sheen finish or alternatively two or three coats will provide a higher sheen finish.

How to Use

R30P is supplied ready to use and should not be diluted. Shake container before use. Ensure surface is thoroughly dry before application. (Applying to a damp surface may cause whitening.) Do not pour directly on to surface.

- Apply with a brush, long pile roller or air-less garden sprayer.
- Apply an even coat avoiding runs, drips or puddling by removing excess product from the surface.
- For porous surfaces, apply 2 coats, the second within 2 hours of the first. PLEASE NOTE - if a natural finish is required only apply one coat to Block Paving.
- DO NOT allow the product to cure in between applications.

Important

This product is not suitable for Natural Stone or Black Limestone. Natural Stone Sealer or Black Limestone Sealer and Restorer should be used in these instances. This product is not suitable if surfaces have been previously treated with a silicone or stearate based water repellent. Do not apply if rain is expected within 4 hours. Do not apply during rain or frost and when surface air temperature is <10°C and > 25°C. Once a fully treated surface is dry R30 cannot be reapplied as there will be a loss of adhesion. Keep pets away until surface is fully dry.

Curing

Allow the product to cure overnight before subjecting to heavy traffic - increase this time in cold, damp conditions. Optimum performance is reached after 2 -3 days.

Precautions for use:

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

Storage

Keep out of reach of children. Keep in a dry place between 5°C and 30°C in the original container.

Cleaning of Equipment

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.



Benefits:

- Can be used on a variety of surfaces including : Patios, Paths, Block Paving, Concrete, Brick, Flagstones and Garage Floors.
- Hard wearing and long lasting.
- Reduces surface degradation
- Enhances surface colour
- UV Resistant
- Non-Flammable.
- Environmentally friendly.
- Fast acting and ready to use

Surface Preparation

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory and to calculate consumption. Allowing the test patch to weather before proceeding to coat the whole area. Remove surface contamination. Surface should be clean, free from dust, dirt, oil, efflorescence, organic growth, coatings and water sealers. All algae and mould should be treated and removed, Enviromose Algae Remover Concentrate is ideal.

Product Characteristics

Colour	White
Odour	Barely Perceptible
Form	Liquid
Application Temperature	Between 5°C and 30°C
Shelf Life	24 Months from the date of manufacture in the original unopened container
PH	7
Specific Gravity @ 25 °C	1.00