



## HIGHLY CONCENTRATED

# Wood Protector

Wood UV Protector is a water based wood treatment, its special formula works to provide superb protection against water and weathering.

Water is repelled from the surface so the timber is dryer for longer periods, this reduces the growth of spores and algae. Ingredients penetrate into the timber to give long lasting protection, available in a variety of colours. Designed as a two coat application.

### Surface Preparation:

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory and to calculate consumption.

Ensure the surface to be treated is dry, clean, free from any contaminants including dust, dirt, oil, grease, algae and mould.

Algae, moss and spores must be treated and removed with a good quality algicide before application, all residues of the algicide need to be removed and allowed to dry before applying the the Wood UV Protector.

For best results first use a power washer to remove the dirt and grime from between the grooves of the decking.

Remove previous coatings such as paint, varnish or stain fully before applying the Decking / Wood Oil.

### How to use:

Supplied ready to use do not dilute.

Shake the container well before use and regularly during application

Ensure surface is thoroughly dry and clean before proceeding.

Do not pour directly onto the surface. Apply a generous even coat with a brush, in the direction of the wood grain. Mop up pooling as you go using a lint free cloth. Ensure you cover all edges for optimum performance.

Allow the first coat to dry, and then apply a second coat. Leave to dry for 24 hours before subjecting to heavy traffic.

### Coverage:

Spread rates vary dependant on the type and age of decking.

- New decking 4-6m<sup>2</sup> per litre
- 3 year old decking 2-4m<sup>2</sup> per litre

### Important information:

Do not apply when ambient/surface temperature is below 10°C or above 25°C. Do not apply in wet weather, when rain is imminent or before surface is completely dry. Keep pets away until surface is fully dry.



### Benefits:

- UV resistant coating for exterior wood
- Suitable for vertical and horizontal surfaces which require protection
- Solvent free and easy to use
- Excellent durability against weathering, helping to prevent swelling, shrinkage, splitting and warping
- Reduces the growth of moss and algae
- Long lasting technology
- Allows the wood to breathe
- Enhances the colour of the decking /wood
- Suitable for rough sawn or smooth timber

### Precautions for use:

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

### Cleaning of equipment:

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.

### Product Characteristics

Colour	Various Colours Available
Odour	Barely Perceptible
Form	Liquid
PH	7
Application Temperature	Between 5°C and 38°C
Shelf Life	24 Months from the date of manufacture in the original unopened container
Specific Gravity @ 25 °C	0.99