



HIGH PERFORMANCE

Pre Grout Protector

The ultimate release agent for tiles and paving. Enables easy removal of grout and jointing compound from the surface to leave a perfect finish. An essential part of any tilers' toolbox removing any potential need to re-grout or re-tile.

Dirt Defence Pre Grout Protector is a water-based emulsion specifically designed to protect tiles prior to grouting. The temporary protective coating protects surfaces against discolouration when using pigmented grouts.

Surface Preparation

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory.

Ensure the surface is clean, dry, sound and free from any dust or debris.

How to use:

Supplied ready to use, do not dilute.
Shake container well before each use

Apply prior to grouting, using a clean pro sponge, brush or roller

Rub well onto the surface, avoid application to joints

Allow 15 minutes for sealer to dry and apply a second coat
Allow to dry for minimum 1 hour (depending on temperature)

Once dry apply grout as required

Some of the sealer will be removed during the washing-off process

Any residual sealer can be removed with clean water and agitation after grouting has set for larger areas a power washer can be used

Precautions for use:

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

Cleaning of equipment:

Cloths can be cleaned immediately after use with soapy water.



Perfect for use on:

- Glazed/unglazed ceramic tiles
- Mosaics
- Terrazzo
- Marble
- Polished Porcelain
- Smooth Natural Stone
- Smooth Terracotta
- Quarry Tiles
- Can be used on walls/floors

Benefits:

- Easy and quick to apply
- Externally and internal use
- Protects the tiled surface from discolouration when pigmented grouts are used
- Easy to remove once grouting complete
- Cost effective

Important information:

Only suitable for Terracotta and Natural Stone Tiles if the surface is smooth.

DO NOT allow product to get into the joints.

DO NOT use in temperatures below 5°C in damp conditions.

Product Characteristics

Colour	Milky
Odour	Barely Perceptible
Form	Liquid
Coverage	24 - 36 m
Application Temperature	Between 5°C and 38°C
Shelf Life	12 Months from the date of manufacture in the original unopened container - protect from frost