

Concrete Block & Paving Sealer SATIN FINISH

- PROTECTS AND WATERPROOFS CONCRETE BLOCK PAVING
- USES MICRO-POLYMER TECHNOLOGY
- ENHANCES LOOK OF EXISTING SURFACES
- THE MORE COATS, THE GLOSSIER THE FINISH
- RESISTS FUNGAL GROWTH AND STAINING

Enviromose Concrete Block and Paving Sealer is a high performance sealcoat formulated to provide a hard wearing and weatherproof seal to block paving, paths and patios. Available in a satin finish, Enviromose Concrete Block and Paving Sealer stabilises the surface, helps repel dirt, oil, fuel stains, enhances the surface finish and inhibits the growth of moss and algae.

BENEFITS

- Protects and waterproofs • Resists fungal growth & staining
- Stabilises sand joints • Enhances look of existing surfaces
- Easy clean and maintenance

BEFORE TREATMENT

Ensure that the surface to be treated is clean and free of any contaminants including oil, grease, algae and efflorescence. On new block paving or paving flags, make sure blocks, flags and jointing sand are dry and jointing sand has been well compacted. This product is not suitable if surfaces have been treated previously with a silicone or stearate based water repellent.

APPLICATION

- Shake container before use
- Ensure surface is thoroughly dry before application
- Do not pour Concrete Block and Paving Sealer directly onto paving
- Use a long pile roller and tray, applying an even coat. Avoid runs or puddles by removing excess product from the surface
- For porous surfaces, apply 2 coats, the second within 2 hours after the first
- For dense surfaces e.g. block paving, a single coat provides a satin finish
- For a higher sheen finish, apply a second or third coat, each within 2 hours of previous application

COVERAGE

4-6m² per litre dependent on the porosity of the surface.

CLEANING

Clean brushes, rollers and other equipment immediately after use with soapy water. Remove as much product as possible from application equipment before cleaning.

STORAGE

24 months from the date of manufacture in original unopened container in a clean, dry area. Do not store below 5°C.



HEALTH & SAFETY

- Keep out of reach of children.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Do not get in eyes, on skin, or on clothing.
- Do not eat, drink or smoke when using this product.
- IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
- IF ON SKIN: wash with plenty of soap and water, get medical advice/attention.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, get immediate medical advice/attention.

IMPORTANT

- Do not apply when ambient/surface temperature is below +10°C
- Do not apply in wet weather, when rain is imminent or before surface is completely dry
- Optimum performance is reached after 2-3 days. Allow product to cure overnight before subjecting to heavy use – increase this time in cold, damp conditions
- Always test a small inconspicuous area before use to ensure surface compatibility, performance and finish/texture is acceptable
- Not suitable for non porous surfaces e.g. quarry tiles, engineering brick, polished or glazed surfaces
- Keep pets away until surface is fully dry
- Protect from frost and store above +5°C in ventilated area away from heat source

