

Concrete Block & Paving Sealer NATURAL FINISH

- PROTECTS AND WATERPROOFS CONCRETE BLOCK PAVING
- USES NANO-PENETRATION TECHNOLOGY
- RESISTS FUNGAL GROWTH AND STAINING
- BREATHABLE & LONG LASTING
- EASY TO CLEAN

Enviromose Block & Paving Sealer is an advanced formula, high performance sealer using the latest flouropolymer technology to provide a waterproof, breathable transparent, durable seal to Block Paving, Paths & Patios. Suitable for limestone and granite. Solvent free and easy to use, Enviromose Block & Paving Sealer helps to repel dirt, oil, stains, grease and inhibits the growth of moss and algae.

BENEFITS

- Long lasting flouropolymer technology • Protects and waterproofs
- Easy to clean • Resists fungal growth & staining

BEFORE TREATMENT

Ensure that the surface to be treated is clean and free of any contaminants including oil, grease, algae and efflorescence. This product is not suitable if surfaces have been treated previously with a silicone or stearate based water repellent.

APPLICATION

- Shake container before use
- Ensure surface is thoroughly dry before application
- Do not pour Enviromose Block & Paving Sealer directly onto paving. Apply by brush, roller or garden sprayer with fan pattern spray attachment, applying an even coat and avoiding runs or puddles by removing excess product from the surface
- Apply 2 coats, the second within 2 hours after the first. Further coats can be applied if required
- **Does not bind sand**

COVERAGE

4-6m² per litre dependent on the porosity of the surface.

CLEANING

Clean brushes, rollers and other equipment immediately after use with soapy water. Remove as much product as possible from application equipment before cleaning.

STORAGE

24 months from the date of manufacture in original unopened container in a clean, dry area. Do not store below 5°C.



HEALTH & SAFETY

- Keep out of reach of children.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Do not get in eyes, on skin, or on clothing.
- Do not eat, drink or smoke when using this product.
- IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
- IF ON SKIN: wash with plenty of soap and water, get medical advice/attention.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, get immediate medical advice/attention.

IMPORTANT

- Do not apply when ambient/surface temperature is below +10°C
- Do not apply in wet weather, when rain is imminent or before surface is completely dry
- Optimum performance is reached after 2-3 days. Allow product to cure overnight before subjecting to heavy use – increase this time in cold, damp conditions
- Always test a small inconspicuous area before use to ensure surface compatibility, performance and finish/texture is acceptable
- Not suitable for non porous surfaces e.g. quarry tiles, engineering brick, polished or glazed surfaces
- Keep pets away until surface is fully dry
- Protect from frost and store above +5°C in ventilated area away from heat source

