

MULTI SURFACE SEALER

Fluorocarbon & PFAS, PFOA, PFOS free

Provides a hard wearing, invisible, protective seal against water, oil, stains, efflorescence and much more on both horizontal and vertical surfaces.

A high performance, penetrating, repellent sealer specifically designed for patios, walls and roofs. Formulated using the latest technology to give outstanding performance and durability with the use of more environmentally preferred ingredients. Forever chemical free formulation.

Surface Preparation

Remove surface contamination and ensure all algae and mould have been treated and removed prior to application. Surface must be completely clean and dry before application.

Important

Non suitable for non absorbent surfaces such as shiny or glazed tiles and stone. Not suitable if the surface has been previously treated with a sealer.

Keep children and pets away until the treatment is complete and the surface is completely dry. Do not apply if rain is expected within 4 hours or before the surface is completely dry. Do not apply to hot surfaces or in direct sunlight.

Application

Always test a small hidden portion of the substrate before use, to ensure the final result is satisfactory and to calculate consumption. Ready to use product, do not dilute.

- Shake container well, apply liberally using a brush, garden sprayer or roller
- Ensure the surface is saturated at a spread rate of 4-6m² per litre. Once the first coat starts to soak in, apply a further wet on wet coat. This method gives deeper penetration into the surface. Do not allow the product to dry between applications
- Avoid runs, drips or puddling by removing excess product from the surface using a clean lint free cloth or dry roller
- Leave to dry. Surface should be touch dry within 4 hours and fully dry after 24 hours. Allow 7 days to reach optimum performance
- For patios and floor areas please allow 24 hours before subjecting to heavy traffic

Cleaning of Equipment

Remove as much excess product as possible and clean tools and equipment immediately after use with soapy water.



Ideal for use on

- Natural stone
- Paths & Patios
- Brick Walls & Render
- Absorbent Roof tiles
- Honed or tumbled stone
- Concrete
- Block paving

Benefits

- Breathable and long lasting
- Non film forming
- Impregnating (non film forming)
- Invisible
- Reduces fungal growth and algae
- UV Resistant
- Non-Flammable
- Free from PFOA, PFOS, Perfluorinated & Polyfluorinated Substances

For Health & Safety instructions, first aid measures, spillages and disposal instructions, see separate Health & Safety Data Sheet (MSDS).

Product Characteristics

Colour	Milky
Odour	Faint
Form	Liquid
Coverage	4 - 6 m ² per litre for absorbent stone, up to 12 m ² per litre for less absorbent stone
Application Temperature	Between 5°C and 30°C
Shelf Life	24 Months from the date of manufacture in the original unopened container
Specific Gravity @ 25 °C	1.01
Curing	Touch dry within 4 hours, allow 7 days to reach full performance